

# DURACELL®



**CEF27NA2, CEF27UK2,  
CEF27EU2**

**Ion Speed 4000 (NA)**

**Hi Speed Advanced (Europe)**

**Duracell Rechargeable**



| Specifications    |                                                                                                                     |
|-------------------|---------------------------------------------------------------------------------------------------------------------|
| Battery Charger:  | Class 2, Integrated Power Supply                                                                                    |
| Plug:             | Direct Plug in Matches Local Requirements                                                                           |
| Battery Type/Fit: | NiMH: 2 or 4 AA/HR6, NiMH: 2 or 4 AAA/HR03                                                                          |
| Typical Weight:   | 121.2g                                                                                                              |
| Input:            | 100-240V AC, 50-60 Hz, 7w                                                                                           |
| Output:           | 2xAA Batteries: min 1550mA<br>4xAA Batteries: min 775mA<br>2xAAA Batteries: min 775mA<br>4xAAA Batteries: min 388mA |
| Operating Temp:   | 0°C - 35°C (32°F - 95°F)                                                                                            |
| Dimensions:       | Open: 140mm x 66mm x 33mm<br>Closed: 77.4mm x 66mm x 33mm                                                           |

|            |                                          |
|------------|------------------------------------------|
| FEATURES   | Charge Time: 1 to 2 ½ hours              |
|            | 4000mW Charge Power                      |
|            | LED Charge Status Indicators             |
|            | Works with all AA and AAA NiMH batteries |
|            | Charges 2 or 4 batteries at a time       |
| INDICATION | Solid Red = Charging                     |
|            | Solid Green = Charged                    |
|            | Blinking Green = Ready to Use            |
|            | Blinking Red = Error/Bad Battery         |
|            | Off = No Battery                         |
| SAFETY     | Over Voltage Protection                  |
|            | Low Voltage Protection                   |
|            | Reverse Polarity Protection              |
|            | Short Circuit Protection                 |
|            | Primary Cell Protection                  |
|            | Over Temperature Protection              |
|            | Low Temperature Protection               |
|            | Overcharge Protection                    |
|            | Safety Timer                             |

Information and contents in this data sheet are for reference purposes only. They do not constitute any warranty and representation is subject to change without notice. For most current information and further details, please contact Duracell.